

Package: metaconfoundr (via r-universe)

September 8, 2024

Title Visualize 'Confounder' Control in Meta-Analyses

Version 0.1.2.9000

Description Visualize 'confounder' control in meta-analysis. 'metaconfoundr' is an approach to evaluating bias in studies used in meta-analyses based on the causal inference framework. Study groups create a causal diagram displaying their assumptions about the scientific question. From this, they develop a list of important 'confounders'. Then, they evaluate whether studies controlled for these variables well. 'metaconfoundr' is a toolkit to facilitate this process and visualize the results as heat maps, traffic light plots, and more.

License MIT + file LICENSE

URL <https://github.com/malcolmbarrett/metaconfoundr>

BugReports <https://github.com/malcolmbarrett/metaconfoundr/issues>

Depends R (>= 3.5.0)

Imports dplyr (>= 1.0.0), forcats, ggplot2 (>= 3.4.0), magrittr, purrr, rlang (>= 0.1.2), shiny, stringr, tibble, tidyr (>= 1.0.0), tidyselect

Suggests covr, knitr, metafor, patchwork, readr, rio, rmarkdown, roxygen2, spelling, testthat (>= 3.0.0), vdiff

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

Language en-US

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.2

Repository <https://malcolmbarrett.r-universe.dev>

RemoteUrl <https://github.com/malcolmbarrett/metaconfoundr>

RemoteRef HEAD

RemoteSha 3af7bc98a79d090d68c79551bcc86cf5b61d2489

Contents

| | |
|-------------------------------------|----|
| count_non_confounders | 2 |
| facet_constructs | 3 |
| geom_cochrane | 3 |
| ipi_data | 4 |
| label_robins | 5 |
| launch_metaconfoundr_app | 6 |
| mc_detect_layout | 6 |
| mc_heatmap | 8 |
| metaconfoundr() | 9 |
| scale_fill_cochrane | 10 |
| score_control | 11 |
| summarize_control_quality | 11 |
| theme_mc | 12 |

Index **14**

count_non_confounders *Count and plot non-confounders*

Description

Count and plot non-confounders

Usage

```
count_non_confounders(.df)
```

```
plot_non_confounders(.df, ..., geom = ggplot2::geom_col, sort = TRUE)
```

Arguments

| | |
|------|-----------------------------------------------------|
| .df | A data frame, usually the result of metaconfoundr() |
| ... | Arguments passed to geom |
| geom | The ggplot2 geom to use |
| sort | Logical. Should the results be sorted? |

Value

a tibble or ggplot

Examples

```
ipi %>%
  metaconfoundr() %>%
  plot_non_confounders(size = 3, geom = ggplot2::geom_point)
```

| | |
|------------------|----------------------------|
| facet_constrcuts | <i>Facet by constrcuts</i> |
|------------------|----------------------------|

Description

A helper function to facet by constructs in `'mc_heatmap()` and `mc_trafficlight()`

Usage

```
facet_constrcuts(...)
```

Arguments

... Arguments passed to `ggplot2::facet_grid()`

Value

a facet component

See Also

Other plots: `geom_cochrane()`, `mc_heatmap()`, `scale_fill_cochrane()`, `theme_mc()`

| | |
|---------------|-----------------------------------------------------------------------|
| geom_cochrane | <i>Add Cochrane-style symbols to heatmaps and traffic light plots</i> |
|---------------|-----------------------------------------------------------------------|

Description

Add Cochrane-style symbols to heatmaps and traffic light plots

Usage

```
geom_cochrane(
  mapping = ggplot2::aes(shape = control_quality),
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE
)
```

Arguments

| | |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mapping | Set of aesthetic mappings created by <code>aes()</code> or <code>aes_()</code> . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping. |
| data | The data to be displayed in this layer. There are three options: If <code>NULL</code> , the default, the data is inherited from the plot data as specified in the call to <code>ggplot()</code> . A <code>data.frame</code> , or other object, will override the plot data. All objects will be fortified to produce a data frame. See <code>fortify()</code> for which variables will be created. A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code> , and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>). |
| stat | The statistical transformation to use on the data for this layer, as a string. |
| position | Position adjustment, either as a string, or the result of a call to a position adjustment function. |
| ... | Other arguments passed on to <code>layer()</code> . These are often aesthetics, used to set an aesthetic to a fixed value, like <code>colour = "red"</code> or <code>size = 3</code> . They may also be parameters to the paired geom/stat. |
| na.rm | If <code>FALSE</code> , the default, missing values are removed with a warning. If <code>TRUE</code> , missing values are silently removed. |
| show.legend | logical. Should this layer be included in the legends? <code>NA</code> , the default, includes if any aesthetics are mapped. <code>FALSE</code> never includes, and <code>TRUE</code> always includes. It can also be a named logical vector to finely select the aesthetics to display. |
| inherit.aes | If <code>FALSE</code> , overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> . |

Value

a geom

See Also

Other plots: `facet_constructs()`, `mc_heatmap()`, `scale_fill_cochrane()`, `theme_mc()`

Description

These data represent 14 analyses (retrospective cohorts and sibling-matched designs) to evaluate the association between short interpregnancy interval (<6 months versus 18-23 months) and risk of preterm birth (<37 weeks gestation) and the adequacy of confounder control (Petersen et al.). Adequacy of confounder control was determined overall for each study as well as by variable and construct (groupings of conceptually related variables). These studies are a subset of studies originally identified in a systematic review by Ahrens et al. to summarize associations between short interpregnancy interval and a variety of perinatal outcomes in high-resource settings.

Usage

```
ipi
```

```
ipi_wide
```

```
ipi_metaanalysis
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 407 rows and 5 columns.

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 37 rows and 14 columns.

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 11 rows and 9 columns.

Source

Ahrens et al. (2019)

References

Ahrens KA, Nelson H, Stidd RL, Moskosky S, Hutcheon JA. Short interpregnancy intervals and adverse perinatal outcomes in high-resource settings: An updated systematic review. *Paediatr Perinat Epidemiol.* 2019;33(1):O25-O47.

Petersen JM, Barrett M, Ahrens K, Murray EJ, Hogue C, Mumford S, Bryant Mantha A, Fox MP, Gadupudi S, Trinquart L. Confounder Matrix: A Tool to Assess Confounding Bias in Systematic Reviews of Observational Studies. 2020

label_robins

Label values using ROBINS approach

Description

`label_robins()` is a helper function to modify metaconfoundr labels to use ROBINS-like labels: low risk, some concerns, high risk.

Usage

```
label_robins()
```

Value

a character vector of ROBINS labels

Examples

```
mc_heatmap(metaconfoundr(ipi)) +
  ggplot2::scale_fill_ordinal(labels = label_robins())
```

```
mc_heatmap(metaconfoundr(pi)) +
  scale_fill_cochrane(labels = label_robins())
```

launch_metaconfoundr_app

Launch metaconfoundr Shiny app

Description

launch_metaconfoundr_app() launches a Shiny app to create visualizations of confounding control in meta-analyses

Usage

```
launch_metaconfoundr_app()
```

Value

A Shiny app

mc_detect_layout

Tidy metaconfoundr data layouts

Description

mc_longer() and mc_wider() are helper functions to put metaconfoundr() for long and wide data sets, respectively. results into a tidy format. mc_detect_layout() chooses between the two automatically based on the number of variables in the data frame. mc_study_values() helps standardize evaluations of control quality.

Usage

```
mc_detect_layout(...)  
  
mc_longer(  
  study = contains("construct"),  
  construct = contains("construct"),  
  variable = matches("variable|factor"),  
  control_quality = contains("control_quality"),  
  is_confounder = contains("confounder"),  
  study_values = mc_study_values()  
)  
  
mc_study_values(inadequate = 0, some_concerns = 1, adequate = 2)  
  
mc_wider(  
  construct = contains("construct"),  
  variable = matches("variable|factor"),  
  is_confounder = contains("confounder"),  
  study = everything(),  
  study_values = mc_study_values()  
)
```

Arguments

| | |
|-----------------|---------------------------------------------------------------------------------------|
| ... | Additional arguments passed to <code>mc_wider()</code> or <code>mc_longer()</code> |
| study | The column with the name of the studies |
| construct | The domain or construct column |
| variable | The column that describes the confounding variables |
| control_quality | The column that describes the confounding control quality |
| is_confounder | The column that describes if a variable is a confounder |
| study_values | What are the levels of control_quality? Use <code>mc_study_values()</code> to set up. |
| inadequate | Which value signifies inadequate control? |
| some_concerns | Which value signifies control with some concerns? |
| adequate | Which value signifies adequate control? |

Value

a function that tidies the data

 mc_heatmap

Plot a heatmap or traffic light plot of metaconfoundr() summaries

Description

mc_heatmap() and mc_trafficlight() visualize the results of metaconfoundr(), summarizing the quality of confounder control in each study.

Usage

```
mc_heatmap(
  .df,
  legend_title = "control quality",
  sort = FALSE,
  by_group = FALSE,
  score = c("adequate", "sum", "controlled"),
  non_confounders = FALSE
)
```

```
mc_trafficlight(
  .df,
  size = 8,
  legend_title = "control quality",
  sort = FALSE,
  by_group = FALSE,
  score = c("adequate", "sum", "controlled"),
  non_confounders = FALSE
)
```

Arguments

| | |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| .df | A data frame, usually the result of metaconfoundr() |
| legend_title | The legend title |
| sort | Logical. Sort by confounder score? Calculated by score_control() |
| by_group | Logical. If sorted, sort within domain? |
| score | The approach used to calculate the score. adequate tests if the study controlled at a strictly adequate level. sum treats control_quality as an ordinal integer, summing it's values such that a higher score has better control overall. controlled tests if any control, including some concerns control, is present. |
| non_confounders | Logical. Include non-confounders? Default is FALSE. |
| size | The size of the points in the traffic light plot |

Value

a ggplot

See Also

Other plots: [facet_constructs\(\)](#), [geom_cochrane\(\)](#), [scale_fill_cochrane\(\)](#), [theme_mc\(\)](#)

Examples

```
ipi %>%
  metaconfoundr() %>%
  dplyr::mutate(variable = stringr::str_wrap(variable, 10)) %>%
  mc_heatmap() +
  theme_mc() +
  facet_constructs() +
  ggplot2::guides(x = ggplot2::guide_axis(n.dodge = 2))
```

```
ipi %>%
  metaconfoundr() %>%
  mc_trafficlight() +
  geom_cochrane() +
  facet_constructs() +
  scale_fill_cochrane() +
  theme_mc() +
  ggplot2::guides(x = ggplot2::guide_axis(n.dodge = 2))
```

 metaconfoundr()

Prepare a meta-analysis data set for metaconfoundr

Description

`metaconfoundr()` standardizes data frames with information on how well a set of studies control for a set of variables. In this approach, a set of domain experts agree on the variables that are required to properly control for confounding for a scientific question. Then, for a given confounder, the studies are described as being adequately controlled, inadequately controlled, or controlled with some concerns. `metaconfoundr()` is intended to standardize data for use in [mc_heatmap\(\)](#) and [mc_trafficlight\(\)](#). See the vignette on data preparation for more information on how to set up your evaluation.

Usage

```
metaconfoundr(.df, data_format = mc_detect_layout())
```

Arguments

| | |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>.df</code> | A data frame. See the vignette on data preparation for more details. |
| <code>data_format</code> | The format of the data. Detected automatically by default, but explicit options include mc_longer() and mc_wider() |

Value

a tibble

Examples

```
metaconfoundr(ipi)

metaconfoundr(ipi_wide)

ipi_wide2 <- ipi_wide %>%
  dplyr::rename(scope = construct)

metaconfoundr(ipi_wide2, mc_wider(construct = "scope"))
```

scale_fill_cochrane *Add Cochrane-style palettes to ggplots*

Description

Add Cochrane-style palettes to ggplots

Usage

```
scale_fill_cochrane(...)

scale_color_cochrane(...)

scale_shape_cochrane(...)
```

Arguments

... Arguments passed to the underline scale function

Value

scales for ggplot

See Also

Other plots: [facet_constructs\(\)](#), [geom_cochrane\(\)](#), [mc_heatmap\(\)](#), [theme_mc\(\)](#)

| | |
|---------------|-------------------------------------------|
| score_control | <i>Add a score of confounding control</i> |
|---------------|-------------------------------------------|

Description

score_control() adds a variable, score, that summarizes how well a study controls for a domain or construct. Used to sort heatmaps and traffic light plots.

Usage

```
score_control(.df, score = c("adequate", "sum", "controlled"))
```

Arguments

| | |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| .df | A data frame, usually the result of <code>metaconfoundr()</code> |
| score | The approach used to calculate the score. adequate tests if the study controlled at a strictly adequate level. sum treats control_quality as an ordinal integer, summing it's values such that a higher score has better control overall. controlled tests if any control, including some concerns control, is present. |

Value

a tibble

Examples

```
library(dplyr)

ipi %>%
  metaconfoundr() %>%
  filter(is_confounder == "Y") %>%
  score_control("controlled") %>%
  arrange(desc(score))
```

| | |
|---------------------------|-------------------------------------------------|
| summarize_control_quality | <i>Summarize the control quality of studies</i> |
|---------------------------|-------------------------------------------------|

Description

summarize_control_quality() allows you to summarize how well studies control for variables within one or more domains, and how well those domains are controlled for overall. Each logical statement is a domain and can be named.

Usage

```
summarize_control_quality(.df, ..., domains = TRUE)
```

Arguments

| | |
|---------|---------------------------------------------------------------------------------------------|
| .df | A data frame, usually the result of <code>metaconfoundr()</code> |
| ... | Boolean arguments to declare adequate control logic |
| domains | Logical. Include the domains in the output? If FALSE, only returns overall control quality. |

Value

A tibble

Examples

```
summary_df <- summarize_control_quality(  
  metaconfoundr(ipi),  
  Sociodemographics = `Maternal age` & `Race/ethnicity` & `Marital status`,  
  Socioeconomics = `SES category` | Insurance & Education,  
  "Reproductive Hx" = `Prior pregnancy outcome`  
)  
  
summary_df  
  
summary_df %>%  
  mc_trafficlight() +  
  theme_mc() +  
  facet_constructs() +  
  geom_cochrane() +  
  scale_fill_cochrane()
```

theme_mc

A minimal theme for metaconfoundr plots

Description

A minimal theme for metaconfoundr plots

Usage

```
theme_mc(base_size = 14)
```

Arguments

| | |
|-----------|-------------------------------|
| base_size | base font size, given in pts. |
|-----------|-------------------------------|

Value

a ggplot theme

See Also

Other plots: [facet_constructs\(\)](#), [geom_cochrane\(\)](#), [mc_heatmap\(\)](#), [scale_fill_cochrane\(\)](#)

Index

- * **datasets**
 - [ipi_data](#), [4](#)
- * **plots**
 - [facet_constructs](#), [3](#)
 - [geom_cochrane](#), [3](#)
 - [mc_heatmap](#), [8](#)
 - [scale_fill_cochrane](#), [10](#)
 - [theme_mc](#), [12](#)
- [aes\(\)](#), [4](#)
- [aes_\(\)](#), [4](#)
- [borders\(\)](#), [4](#)
- [count_non_confounders](#), [2](#)
- [facet_constructs](#), [3](#), [4](#), [9](#), [10](#), [13](#)
- [fortify\(\)](#), [4](#)
- [geom_cochrane](#), [3](#), [3](#), [9](#), [10](#), [13](#)
- [ggplot\(\)](#), [4](#)
- [ggplot2::facet_grid\(\)](#), [3](#)
- [ipi \(ipi_data\)](#), [4](#)
- [ipi_data](#), [4](#)
- [ipi_metaanalysis \(ipi_data\)](#), [4](#)
- [ipi_wide \(ipi_data\)](#), [4](#)
- [label_robins](#), [5](#)
- [launch_metaconfoundr_app](#), [6](#)
- [layer\(\)](#), [4](#)
- [mc_detect_layout](#), [6](#)
- [mc_heatmap](#), [3](#), [4](#), [8](#), [10](#), [13](#)
- [mc_heatmap\(\)](#), [3](#), [9](#)
- [mc_longer \(mc_detect_layout\)](#), [6](#)
- [mc_longer\(\)](#), [9](#)
- [mc_study_values \(mc_detect_layout\)](#), [6](#)
- [mc_trafficlight \(mc_heatmap\)](#), [8](#)
- [mc_trafficlight\(\)](#), [3](#), [9](#)
- [mc_wider \(mc_detect_layout\)](#), [6](#)
- [mc_wider\(\)](#), [9](#)
- [metaconfoundr \(metaconfoundr\(\)\)](#), [9](#)
- [metaconfoundr\(\)](#), [6](#), [9](#), [11](#), [12](#)
- [plot_non_confounders \(count_non_confounders\)](#), [2](#)
- [scale_color_cochrane \(scale_fill_cochrane\)](#), [10](#)
- [scale_fill_cochrane](#), [3](#), [4](#), [9](#), [10](#), [13](#)
- [scale_shape_cochrane \(scale_fill_cochrane\)](#), [10](#)
- [score_control](#), [11](#)
- [score_control\(\)](#), [8](#)
- [summarize_control_quality](#), [11](#)
- [theme_mc](#), [3](#), [4](#), [9](#), [10](#), [12](#)